



250R

POA

## Specifications

### Boat Details

Price POA  
Model 250R  
Year 2024  
Hull Style  
Power Type  
Condition New  
Suburb PIALBA

Boat Brand Mercury  
Length 0.00  
Category Boat Engines and Outboards  
Hull Type  
Stock Number 0  
State Queensland  
Engine Make Mercury

### Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.



Phone: 07 4128 9944

Email: [sales@baycitymarine.com.au](mailto:sales@baycitymarine.com.au)

57 Islander Road Pialba QLD 4655

---

## Description

The 250R FourStroke pumps out 250 propshaft horsepower. The stout V-8 powerhead provides an astounding 53% increased displacement and up to 40% higher overall bottom-end torque than the legacy two-stroke 250XS it replaces. Transient spark calibration boosts torque by 7% for unmatched acceleration. Advanced Range Optimisation (ARO) automatically adjusts fuel delivery for up to 10% improvement in cruise-speed fuel efficiency. All of this on regular 91-RON Unleaded fuel, while maintaining a comparable weight to the 250 XS. Specifications

- RATED HORSEPOWER (HP/KW) 250/186
- BORE & STROKE (IN/MM) 3.6 x 3.4/92 x 86
- IDLE RPM 600
- MAX RPM AT FULL THROTTLE 5800-6200
- CYLINDERS/ENGINE CONFIGURATION V-8 (64 degree) with 32-valve Dual Overhead Cam (DOHC)
- DISPLACEMENT (LITER/CID) 4.6/279
- INDUCTION SYSTEM Performance-Tuned Long Runner Intake Manifold
- FUEL SYSTEM Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization
- FUEL REQUIREMENTS Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON
- IGNITION SYSTEM SmartCraft PCM 112 Digital Inductive
- CHARGING SYSTEM 85-amp (1071 Watt)
- STARTING Electric Start with SmartStart Protection
- LUBRICATION SYSTEM Integrated wet sump
- OIL REQUIREMENT NMMA Certified FCW SAE 10W-30
- THROTTLE AND SHIFT CONTROLS Mechanical
- MIDSECTION DESIGN Tri-Ram Midsection with High-Durometer Elastomer Upper Mount and Solid Lower Mounts
- SHAFT LENGTH (IN./MM.) 20/508
- GEARCASE Sport Master
- GEAR RATIO 1.75:1
- WEIGHT (LBS./KGS.) 520/236
- WARRANTY 3-Year Limited

---

## Engine Details

Engine Make

Mercury

---

### Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.