



VF250

POA



Specifications

Boat Details

Price	POA	Boat Brand	Yamaha
Model	VF250	Length	0.00
Year	2025	Category	Boat Engines and Outboards
Hull Style		Hull Type	
Power Type	Power	Stock Number	VF250LA
Condition	New	State	Queensland
Suburb	PIALBA	Engine Make	

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.



Description

For sheer unbridled power, speed and performance, Yamaha's VF250 Vmax SHO (Super High Output) four-stroke outboards deliver where no other four-stroke or two-stroke can. This race bred outboard has been purposely designed to meet the competitive needs of bass boat fishing, skiing, racing and other adrenalin packed boating activities. The 4.2 litre, 24-valve, double overhead cam engine is not only extremely compact, but is lighter than another equivalent four-stroke on the market. The secret to its performance is the plasma-fused sleeveless cylinders which significantly reduce the overall weight while increasing the engine capacity. If speed is your thing, then there is no better option.

VMAX SHO's have been engineered specifically to deliver unrivalled hole-shot and acceleration, with an equally impressive top-end speed. Our new V6 VMAX SHO ® outboards not only look great with their aggressive styling upgrades, redesigned cowling and eye-catching raised graphics, these high-performance engines also incorporate some great new features including Yamaha's TotalTilt™ trim system, as seen on our new V6 Offshore range. We have also increased the alternator output by a massive 40%, now producing 70 gross charging amps, enough to power an extensive range of electronic devices.

Technical Specification

HeightL: 493 [19.4] | X: 643 [25.3]

WeightL: 229 | X: 252

EngineFour stroke, 24-Valve, DOHC, Direct Action V6 60°

Displacement4169.0

Bore96 x 96

Max RPM5000-6000

LubricationWet-sump

FueEFI

IgnitionTCI

StarterElectric

Alternator12V - 70A with Rectifier Regulator

OperationMechanical control

TiltPower Trim & Tilt with TotalTilt™

GaugesOptional

Network GaugesOptional

Gear Ratio1.75 : 1

Engine Details

Horse Power

250

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.